



Lease a Z MASTER® 7500-D From \$1,799/month





Looking for a workhorse mower that's easy to operate & gets the job done faster?

- Massive 144-inch wing deck handles your biggest jobs in half the time, then folds up neatly for fast & easy transport up to 27 KM/H
- Mow up to 13 acres/hour with a mowing speed of up to 16 KM/H
- Contour-following wing decks deliver an unmatched quality of cut
- Ride in comfort with the deluxe suspension iso-mount seat



Contact us to learn more

salesinquiries@turfcare.ca







CONTOUR-FOLLOWING WING DECKS

Wing decks on the 96" model flex up 20° and down 15° to follow the terrain, hugging the ground for the smoothest possible cut. Folds to 72.5" to fit in trailer.



THE NEW STANDARD IN COMFORT

The floor pan and deluxe suspension seat are iso-mounted to reduce vibration. That results in a better operator experience and more productivity.



EXTENDED SERVICE INTERVALS Save

on maintenance with extended service intervals and a deck design that uses up to four matching blades. The mower is also backed by a 5-year, 1,500-hour limited warranty (first two years no-hour-limit).



SUPERIOR PERFORMANCE

Whether you choose a Yanmar diesel engine or a Kohler 38 HP EFI gas engine, your mower is packed with power to tackle the toughest mowing jobs.

								ZI	MASTER [®]	7500 SE	RIES							
	HORIZON™ TECHNOLOGY														HORIZON™ T W/OR	ECHNOLOGY PACLE		
	720	28†	720	129†	720	027	72	030	720	76 [†]	720)74 [†]	720)98†	740	090		144
POWER SYSTEM		-																
Commercial Engines at 3600 RPM*			25	hp Yanmar°	*Diesel 1267cc										▶ 38 hp Kohler* EFI			
Heavy-Duty Canister										ion System with Electronic Vacuum Sensor							150	occ
Air Cleaner								2" – 12"	-,						24" x 1	2" – 12"	▶ 26" x	12" – 12"
Drive Tires	(66.0 x 30.5 x 30.5 cm)												(61.0 x 30.5	5 x 30.5 cm) 6" Flat-Free	(66.0 x 30.5			
Caster Tires	15" x 6" – 6" Flat-Free Semi-Pneumatic (38.1 x 15.2 x 15.2 cm)												Semi-Pr (33 x 16.5	neumatic x 15.2 cm)	Semi-Pr (38.1 x 15.2	neumatic 2 x 15.2 cm)		
Fuel/Capacity					Diesel/12.5-Gal (47.3 L)											e/12-Gal .4 L)		12.5-Gal 3 L)
Hour Meter	Horizon Technology																	
Hydraulic Drive System	17.84 cu in Hydro-Gear HGM-H Motors with 18cc Kanzaki [*] Pump												Unitized 16cc Pumps 17.84 cu in Hyr & Wheel Motors HGM-H Moto w/Cooling Fans 18cc Kanzak			otors with		
Max Ground Speed (Fwd)	12.5 mph (20.1 km/h)										11.5 mph ((18.5 km/h)	10/17 (16.1/27	mph .4 km/h)				
Clutch					Wet Disc										Electror	magnetic		Disc
MOWING DECKS																		
Deck Size	60" (152 (Poor Die		▶ 72" (1 (Poor Di		60" (15	2.4 cm)	72" (18	(2.9 cm)	72" (18	2.9 cm)	72" (18		▶ 96" (2			3.8 cm) scharge)	▶ 144" (3	365.7 cm) scharge)
Cutting Deck	(Rear Discharge) (Rear Discharge) ou (192.4 cm) /2 (102.9 cm) /2 (102.9 cm) (Rear Discharge) (Rear Discharge) 7-Gauge TURBO FORCE*									scriar ge/	(Iteal Di	scriar ye,	(Real Di	scriar ge/				
Bullnose Bumper		7-Gauge FORCE Standard																
Deck Depth									5.5"	(14.0 cm)								
Adjustable Discharge Baffle	N/A				Standard								N/A					
Rubber Discharge Chute	N/A				Standard						N/A							
Deck Lift Design	Hydraulic with Rocker Switch																	
Spindle Housings								9" (2	2.9 cm) Dian	neter Cast A	luminum							
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard																	
Spindle Bearings									Mainte	nance-Free								
Cutting Height									1.0" – 5.5"	(2.5 – 14.0 c	m)							
Blades					3 blades at 20.5" length								4 blades at 24.5" length				6 bla 24.5"	
Blade Tip Speed	18,200+ ft/min				▶ 18,500+ ft/min									18,100	18,100+ ft/min 18,500+ ft/min			
Shaft Drive					Standard													
Anti-Scalp Rollers	4 Standard, 2 Side Skids				6 Standard 4 Standard, 2 Side Skids								13 Standard					
FEATURES		2 3100	Skius								2 5100	Skius	!					
Steering Controls							1-	-5/8" (4.1 cn	n) Diameter	Grips; Adjus	stable, Dam	pened						
Operator Seat								Delux	e Suspensio	n (Iso-Mour	t, Flip-Up)							
Armrests	Deluxe Suspension (Iso-Mount, Flip-Up) Standard																	
Seat Suspension System	Standard																	
Folding ROPS	Standard																	
Cooling Fans								1	N/A								▶ Sta	ndard
Storage Compartment									Sta	andard								
Floor Pan									Flip-Up	, Iso-Mount								
WEIGHTS AND MEASU																		
Weight	1,957 lbs.		1,964 lbs.			901.3 kg						972 kg		1,202 kg	2,584 lbs.	1,172 kg	3,270 lbs.	1,483 kg
ROPS Height (Folded)	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm
ROPS Height (Upright)		182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm
Deck Width	66.3"	186.4 cm	78.3"	198.9 cm	61.4"	156.0 cm	73.4"	186.4 cm	73.6"	186.9 cm	78.3"	198.9 cm	102.3"	259.8 cm	102.3"	259.8 cm	144.9"	368.1 cm
Deck Width - Wings Up	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	73"	185.4 cm	73"	185.4 cm	83"	210.8 cm
Deflector Width	N/A	N/A	N/A	N/A	72.8"	184.9 cm	84.9"	215.6 cm	87.6"	222.5 cm	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Length	96.48"	245.1 cm	100.68"	255.7 cm	99.68"	245.1 cm	99.6"	253.0 cm	99.68"	245.1 cm	100.68"	255.7 cm	97.38"	247.3 cm	97.38"	247.3 cm	101.3"	257.3 cm

^{*} The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. ¹CARB compliant model or model available.

= Step Up Feature